

AMENDMENTS TO THE CLAIMS

1. (Canceled)

2. (Currently amended): A method for estimating the precision of measurements taken from a gene expression microarray ~~an array~~, comprising:

- (a) identifying a set of low-level data measurements;
- (b) estimating a standard deviation, σ_ϵ of an additive error component, ϵ ;
- (c) estimating a background parameter, α ;
- (d) identifying a set of replicated high-level data measurements;
- (e) estimating a standard deviation, σ_η , of a proportional error component, η

from the standard deviation of the logarithm of the replicated high-level data set;

(f) measuring a signal, y , wherein said signal indicates an amount of a biological molecule; and

- (g) estimating a variance of the measured signal as

$$Var\{y\} = \mu^2 e^{\sigma_\eta^2} (e^{\sigma_\eta^2} - 1) + \sigma_\epsilon^2$$

wherein μ is the amount of the biological molecule and

$$y = \alpha + \mu e^\eta + \epsilon$$

and wherein said identifying step (a) comprises the use of a thresholding algorithm to establish a cutoff, and the set of low-level data consists of those data with values less than the cutoff.

3. (Currently amended): The method of claim 2, wherein the thresholding algorithm comprises the steps of:

(a) identifying A_N , an initial set of low-level data measurements consisting of q percent of the total number of data points having the lowest measurement values, $A_N = \{x_1, x_2, \dots, x_{no}\}$;

- (b) calculating a mean and a standard deviation of the initial set;

(c) calculating a cutoff point, $u_N = \text{mean} + (c \times \text{the standard deviation})$,
 wherein c is the number of standard deviations or mean absolute deviations above the
mean or median and c is set at 2, 2.5 or 3 for each iteration of the thresholding algorithm
 $2 \leq c \leq 3$;

(d) defining a new set, $A_{N+1} = \{x_j < u_N\}$;

(e) calculating a mean and standard deviation of the new set; and

(f) repeating steps (c) and (d) using the mean and standard deviation of the
 new set until the algorithm converges.

4. (Currently amended): The method of claim 2, wherein the thresholding
 algorithm comprises the steps of:

(a) identifying A_N , an initial set, of low-level data consisting of q percent of
 the total number of data points having the lowest measurement values, $A_N = \{x_1, x_2, \dots,$
 $x_{no}\}$;

(b) calculating a median of the initial set, $m_0 = \text{median} \{x_j\}_{j=1}^{n_0}$ and a median of
 the absolute deviations about the median, $MAD_0 = \text{median} \{|x_j - m_0|\}_{j=1}^{n_0}$;

(c) calculating a cutoff point, $u_0 = MAD_0 + (c \times s_0)$, wherein $s_0 = MAD_0/0.675$
 and c is the number of standard deviations or mean absolute deviations above the mean or
median and c is set at 2, 2.5 or 3 for each iteration of the thresholding algorithm $2 \leq c \leq 3$;

(d) defining a new set, $A_{N+1} = \{x_j < u_N\}$;

(e) calculating a median and a median of the absolute deviations about the
 median of the new set; and

(f) repeating steps (c) and (d) using the median and the median of the absolute
 deviations about the median of the new set until the algorithm converges.

5. (Original): The method of claim 2, wherein the mean of the low-level data
 measurements is used as the estimate of the background parameter, α .

6. (Previously presented): The method of claim 2, wherein the standard deviation of the low-level data measurements is used as the estimate of the parameter σ_e .

7. (Previously presented): The method of claim 2, wherein a mean of negative control data is used as the estimate of the background parameter, α .

8. (Previously presented): The method of claim 2, wherein the biological molecule is a nucleic acid.

9. (Original): The method of claim 8, wherein the nucleic acid is mRNA.

10. (Original): The method of claim 8, wherein the biological molecule is DNA.

11. (Original): The method of claim 10, wherein the DNA is cDNA.

12. (Original): The method of claim 10, wherein the DNA is genomic.

13. (Canceled)

14. (Canceled)